



US007103428B2

(12) **United States Patent**  
**Varone et al.**

(10) **Patent No.:** **US 7,103,428 B2**  
(45) **Date of Patent:** **Sep. 5, 2006**

(54) **REMOTE DISPLAY MODULE**

(75) Inventors: **John J. Varone**, Seekonk, MA (US);  
**Timothy Clish**, Taunton, MA (US);  
**John Burroughs**, Exeter, RI (US);  
**Louis Genatossio**, Shrewsbury, MA  
(US); **Rama Machireddy**, Foxboro,  
MA (US); **Norbert W. Elsdorfer**,  
Warwick, RI (US); **Joseph Chopy, Jr.**,  
Cumberland, RI (US)

(73) Assignee: **Brooks Automation, Inc.**, Chelmsford,  
MA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/071,996**

(22) Filed: **Mar. 4, 2005**

(65) **Prior Publication Data**

US 2005/0197722 A1 Sep. 8, 2005

**Related U.S. Application Data**

(63) Continuation of application No. 10/136,908, filed on  
May 1, 2002, now abandoned, which is a continua-  
tion-in-part of application No. 10/023,450, filed on  
Dec. 17, 2001, now abandoned.

(51) **Int. Cl.**

**G05B 15/00** (2006.01)  
**G05B 11/01** (2006.01)  
**G09G 5/00** (2006.01)  
**G06F 3/00** (2006.01)  
**G06F 9/00** (2006.01)  
**G06F 17/00** (2006.01)

(52) **U.S. Cl.** ..... **700/83; 700/17; 700/19;**  
**345/1.2; 345/3.1; 715/736; 715/740; 715/746;**  
**715/864; 715/866**

(58) **Field of Classification Search** ..... 700/2-4,  
700/17, 19, 20, 83, 84; 345/1.2, 3.1; 715/733,  
715/740, 744-747, 864, 866; 341/22, 23  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,622,635 A 11/1986 Chandra et al.  
4,918,930 A 4/1990 Gaudet et al.  
5,157,928 A 10/1992 Gaudet et al.  
5,343,708 A 9/1994 Gaudet et al.  
5,443,368 A 8/1995 Weeks et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

EP 385200 A2 9/1990

(Continued)


*Primary Examiner*—Crystal J. Barnes

(74) *Attorney, Agent, or Firm*—Hamilton, Brook, Smith &  
Reynolds, P.C.

(57) **ABSTRACT**

A portable display unit includes a serial port to connect to a device such as a vacuum network controller, cryopump, turbomolecular pump, gauges or compressor. In particular, the display unit can be plugged and unplugged to devices of different types. The portable display unit includes a display and control keys for programming, controlling and monitoring the functions of a device. The device accessible to the display unit includes a display interface having software code and files to interface with the display unit. Accordingly, the portable display unit can be used with any device having software code to interface with the display unit. The software code generates, refreshes and communicates menus to the portable display unit to provide graphical interface of the device's functions. The portable display unit further includes inner and outer hand grips so that the display unit can be held by hands of different sizes. The hand grips allow user with different hand sizes to firmly hold and navigate the display using control keys with fingers.

**24 Claims, 20 Drawing Sheets**



# US 7,103,428 B2

Page 2

## U.S. PATENT DOCUMENTS

5,450,079 A 9/1995 Dunaway  
5,450,316 A 9/1995 Gaudet et al.  
5,650,940 A 7/1997 Tonozyuka et al.  
5,731,974 A 3/1998 Pietzsch et al.  
5,839,097 A 11/1998 Klausner  
5,889,671 A 3/1999 Autermann et al.  
6,022,195 A 2/2000 Gaudet et al.  
6,029,072 A 2/2000 Barber  
6,203,498 B1 3/2001 Bunce et al.  
6,272,400 B1 8/2001 Jankins et al.  
6,318,093 B1 11/2001 Gaudet et al.  
6,400,462 B1 6/2002 Hille  
6,560,492 B1 5/2003 Borders

6,594,548 B1 7/2003 Bagnordi  
6,628,257 B1 9/2003 Oka et al.  
6,669,600 B1 12/2003 Warner  
6,930,730 B1 \* 8/2005 Maxon et al. .... 348/734  
2001/0052942 A1 12/2001 MacCollum et al.  
2002/0035404 A1 3/2002 Ficco et al.  
2002/0047774 A1 \* 4/2002 Christensen et al. .... 340/3.54  
2003/0033026 A1 2/2003 Murphy  
2003/0114942 A1 \* 6/2003 Varone et al. .... 700/83  
2003/0141987 A1 7/2003 Hayes

## FOREIGN PATENT DOCUMENTS

WO WO 97/04370 2/1997

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B






FIG. 5C




FIG. 6





FIG. 7






FIG. 8B




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A




FIG. 10B






FIG. 10C




FIG. 10D




FIG. 11A




FIG. 11B





FIG. 11C



1

**REMOTE DISPLAY MODULE****RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 10/136,908, filed May 1, 2002, which is a continuation-in-part of U.S. application Ser. No. 10/023,450, filed Dec. 17, 2001. The entire teachings of the above applications are incorporated herein by reference.

**BACKGROUND OF THE INVENTION**

A cluster tool for semiconductor processing generally includes a tool host controller providing top-level control over all systems within the cluster tool. The tool includes a series of processing chambers for performing various semiconductor-fabrication processes such as wafer etching, chemical or plasma vapor deposition, oxidation, sintering, and annealing. These processes often are performed in separate chambers, each of which may include a vacuum system. The vacuum system may include control pads or display units fixed to the devices in the system to provide user interface.

One type of vacuum system that is widely used in semiconductor processing is a cryogenic vacuum system. The cryogenic vacuum system typically includes at least one cryogenic vacuum pump (cryopump) and at least one compressor for supplying compressed helium to the cryopump. The system also often includes other components such as roughing pumps, waterpumps, turbopumps, chillers, valves and gauges. Together, these components operate to provide vacuum to a broader system such as a cluster tool for semiconductor processing.

In addition to the cryopumps, a conventional vacuum system typically includes a network interface terminal which communicates to a tool host controller and the network of cryopumps within the system. The network interface terminal includes an electronic module to monitor and control the devices and components within the network. Similarly, a cryopump may include an electronic module to monitor and control the cryopump.

The electronic modules of the cryopump and network interface terminal may each include a control pad having a keyboard and display. For example, an alphanumeric display displays one line of up to sixteen characters. Longer messages are accessed by horizontal scroll keys. Additional lines of messages and menu items may be displayed by vertical scroll display keys. The keyboard includes numeric keys to input numerical data into the system and functional keys such as ENTER and CLEAR keys to enter and clear data during programming. The keyboard also includes other functional keys to activate device operations. For example, a MONITOR function key allows the display of sensor data and on/off status of the pump and relays. A REGEN function key activates a complete cryopump regeneration cycle, allows regeneration program changes and sets power failure recovery parameters.

**SUMMARY OF THE INVENTION**

A display unit of one embodiment of this invention includes a display, control keys including UP, DOWN and ENTER keys, a device interface for communicating with a device, such as a vacuum controller, and electronic circuitry. The electronic circuitry receives and displays menus received in messages from the device. The electronic circuitry forwards messages to the device when a control key

2

is activated. The display unit stores, modifies and displays data entered with the control keys and forwards the data to the device.

The display unit further includes volatile memory such as RAM to store data entered with control keys but not yet activated or forwarded to the device. The display unit also includes non-volatile memory such as Flash to store software code. The control keys may also include BACK, HOME and HELP keys to support navigation of menus. The display may also include a filter for a clear view of the display.

The display unit may include a rest stand which pivots from the unit to support the display unit in a range of positions. The display unit can be mounted on a tripod using a camera-type screw connector at the bottom of the display unit or to a bracket. The display unit may include a shock mount for protecting the display. Furthermore, the display unit includes inner and outer hand grips on the back panel. The hand grips allows secure holding of the display unit for hands of different sizes. Also, the hand grips are located at both ends of the display unit so that the display unit can be held by either the left or right hand and navigate menus using the control keys with the other hand. The control keys and hand grips are positioned so that the user may hold the display unit with both hands and navigate with a thumb. In addition, the hand grips stabilize and balance the display unit when placed on a flat surface. Accordingly, the display unit is portable and easy to carry around. In addition, the ability to place and hold the display unit in various positions and angles provide optimum viewing angle of the display.

A device to which the display unit is coupled includes a display interface to connect to the display unit. The device also includes a processor and a computer readable medium storing computer executable software code. The device interface and the computer readable medium are in communication with the processor. The software code stored on the device has the capability to perform the following operations: providing a display driver to communicate with the display unit; generating menus specific to the device; and providing a data interface to request and receive data from the device. The device may be a vacuum network controller, cryopump, compressor, roughing pump or turbopump which may be used in a fabrication plant.

A method of this invention includes the steps of connecting the portable display unit to a device and initializing the display unit. The device generates menus and communicates the menus to the display unit. The display unit forwards a key entry to the device. At the device, the key entry is received and processed to generate a second menu. The second menu is communicated to the display unit. Each of the devices to which the display unit may be coupled may include a display controller, including software code, to generate display menus specific to the device.

A method of use includes providing a portable display unit and connecting the portable display unit to a first device of a first type. The display unit receives menus from the first device, displays the menus, and forwards messages to the device to indicate activation of control keys. Similarly, the method includes connecting the display unit to a second device of a second type. The display unit receives menus from the second device, displays the menus, and forwards messages to the device to indicate activation of control keys.

A display unit may be connected to a vacuum network controller via an interface such as a serial port. Similarly, the display unit also may be directly connected to a device such as a cryopump, a roughing pump, a compressor, or a turbopump. The vacuum network controller performs an

3

initialization routine to assure that there is a proper connection between the vacuum network controller and the display unit. During an initialization process, bitmaps specific to the vacuum network controller may be downloaded to the display unit. Also, the vacuum network controller may check the software on the display unit and update the software if the vacuum network controller finds it to be a different version.

Once the vacuum network controller generates menus, the vacuum network controller communicates the menu to the display unit. The vacuum network controller also includes a display driver to communicate with the display units. The display unit receives the menu and displays the menu on the display. When a control key is pressed and activated, the display unit forwards messages to the vacuum network controller. Similarly, a device connected to a display unit performs the functions described above of the vacuum network controller.

In general, the display unit has two key press modes, polling and non-polling. In a polling mode, the key entry is not sent until a device requests a key entry from the display unit. In a non-polling key press mode, the key entry is sent immediately upon key entry. After the key entry is received at the device, the device processes the key entry and generates a second menu. Depending on the type of the first menu, a second menu is a new menu or the same menu with change in data or refreshed data.

Accordingly, the display unit of the present invention provides a stand alone display unit that is compatible with many vacuum system components and other devices. In particular, the display unit includes control keys and display that support menus for all the functions of a device to which the display unit is connected. In addition, a large display facilitates navigation of menus and messages on the display. A high resolution of the display provides a clear view of the display.

Further, the display unit provides control keys that are easy to use and hand grips for holding and stabilizing on a flat surface. The rest stand and screw connector for standing and mounting respectively allow the display to be view in wide range of positions and angles.

### BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects, features and advantages of the invention will be apparent from the following more particular description of preferred embodiments of the invention, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention.

FIG. 1 is a block diagram of a cryogenic vacuum network;

FIG. 2 is a front view of a display unit;

FIG. 3 is a block diagram of the hardware in the display unit of FIG. 2;

FIG. 4 is a rear view of the display unit of FIG. 2;

FIGS. 5A–5C are pictorial diagrams of FIG. 2 illustrating handgrips and use of handgrips;

FIG. 6 is a view of the display unit of FIG. 2 illustrating a rest stand;

FIG. 7 is a view of the display unit of FIG. 2 mounted on a tripod;

FIG. 8A–8B are flowcharts illustrating the processing steps performed between a device and a display unit in a method of this invention;

FIGS. 9A–9C are examples of menus;

4

FIG. 10A–10D are an example tree map diagram of vacuum network controller menus; and

FIGS. 11A–11D are example tree map diagrams of cryopump controller menus.

### DETAILED DESCRIPTION OF THE INVENTION

A description of preferred embodiments of the invention follows.

FIG. 1 is a block diagram of a vacuum network. The vacuum network includes a vacuum network controller 12 which is generally connected to a tool host controller which controls the operation of a cluster tool for semiconductor processing. The tool host controller controls the operation of all processes (e.g., etching, chemical vapor deposition, physical vapor deposition, and annealing) performed within the cluster tool as well as the operation of the vacuum network.

The vacuum network further includes component links 13-1, 13-2 which connect network vacuum system components, such as a cryopump 18, a roughing pump 14, a waterpump 19, a compressor 16, gauges 17 and a turbopump 15. The status of each of these components can be monitored and controlled by the vacuum network controller 12. The vacuum network controller also may include a variety of sensors, including a residual gas analyzer, an ion gauge, and a capacitance. The vacuum network controller 12 in a vacuum network may be that described in U.S. Pat. No. 6,272,400 B1, issued Aug. 7, 2001, entitled “Vacuum Network Controller,” by Jenkins et al., the entire contents of which are incorporated herein by reference.

The display unit 10 is a portable hand held device that may be connected to any of the devices and is powered by the device to which it is connected. The remote display unit 10 provides an user interface to program, control and monitor all functions of the device to which the display unit 10 is connected. For example, as will be discussed in greater detail, the remote display unit 10-1 is connected to the vacuum network controller 12 via display link 11-1 to monitor status, control setup, and program functions of system components/devices connected to the vacuum network controller 12. The display unit 10-5 also can be directly connected to a cryopump 18 through a display link 11-5 to program, control and monitor all cryopump functions using the control keys and display. Similarly, FIG. 1 illustrates a waterpump 19, a turbopump 15, gauges 17, a compressor 16 and a roughing pump 14 connected to respective remote display units 10-2, 10-3, 10-4, 10-5, 10-6, 10-7 through display links 11-2, 11-3, 11-4, 11-5, 11-6, 11-7.

The display unit 10 acts primarily as a slave taking commands from the device. Source code and files to implement this functionality reside on the device. The display unit 10 has some functionality built in to keep the interface simple. However, the display unit 10 can send key presses to the device and the device sends acknowledgment and other messages in response to the key press.

FIG. 2 is a frontal view of the display unit 10 of FIG. 1. The display unit 10 includes a display 24 and control keys 202, 204, 206, 208, 210, 212, 214, 216. The display may have a resolution of about 128×64 pixels to support alphanumeric characters and bitmaps of 21 characters wide and 8 lines high. The control keys include up 208, down 210, left 214 and right 212 arrow scroll keys that are used to navigate around and within the display 24 to change values on the display 24. A selector character such as a right arrow image



may be displayed to support the navigation of the display using the arrow scroll keys **208**, **210**, **212**, **214**.

The display unit **10** further includes function keys such as HOME **202**, BACK **204**, HELP **206** and ENTER **216**. These function keys may be labeled with symbols to indicate their functions.

An ENTER key **216** is in the center of the arrow keys **208**, **210**, **212**, **214** and has multiple functions depending on the screen/menu being displayed. Preferably, the ENTER key **216** allows a user to choose a new menu to be displayed, change a value and commit the changed value. For example, if the menu includes options to different menus, then the user may change to a new menu by selecting the new menu and pressing the ENTER key **216**. In other menus in which a selected value is displayed, such as the BAUD rate of a communication port, the ENTER key **216** allows to modify and commit to a different value.

A HOME key **202** allows the user to return to a main menu from any of the menus being displayed. A BACK key **204** is used to return to the previously displayed menu. If the BACK key **204** is hit while the user is scrolling data to modify the value, then the data is returned to its original value. A HELP key **206** provides additional information about the menu being displayed. The HELP key **206** generates a help menu having additional information. The user may return to the menu from which additional information was requested by hitting the BACK key **204**.

The display unit **10** includes a serial port to provide a connection to a vacuum network device. In addition, the serial port provides power to the display unit **10**. For example, the serial port may be a RS-232 port using a USB cable **26** to connect to the device. The display unit **10** also includes front panel recesses **28-1**, **28-2** on each side of the display **24** to set the display **24** back from the front panel **27** of the display unit **10** for protecting the display from scratching or breaking. The display may be a vacuum fluorescent display having a filter over the display to protect the lens and minimize glare.

In addition, as will be discussed in greater detail, a pivotable rest stand **22** supports positioning of the display unit **10** in various angles. As illustrated in FIG. 2, the rest stand **22** also may be set in a vertical position for securely placing the display unit **10** on a horizontal plane or holding with a hand.

The display unit **10** also has a screen saver mode to increase the life of the display **24**. In particular, the screen saver mode protects the display by preventing phosphorous burnout. When the display unit is idle for a set time, preferably about 15 minutes, the display unit goes into the screen saver mode. The set time is user programmable, and thus can be changed by the user. In this mode, the display **24** dims to the lowest brightness level and scrolls horizontally from left to right across the display **24**. The display unit exits the screen saver mode upon any key press. The display **24** then returns to its normal brightness and stops the scrolling.

A block diagram of the hardware structure of a display unit **10** is provided in FIG. 3. A data bus **39** and address bus **37** link each of the illustrated elements and support data communication.

The display unit **10** further includes a processor **38** which drives the operations of the display unit **10**. In one embodiment, the processor **38** is a Motorola microcontroller running at a maximum speed of about 8 Mhz.

Non-volatile memory **33** includes 512 K bytes of memory and volatile memory **36** includes about 128 K bytes of memory. The non-volatile memory **33** stores display and communication features to lessen the burden on the con-

nected device. For example, a character generator and code to handle a cursor, blinking character strings, scrolling features, selector character, and control key modes may be stored in the non-volatile memory. This allows the device to simply send character strings and the display unit generates characters. In addition, the non-volatile memory **33** also supplies the processor **38** with modules for performing a diagnostic process.

A serial port **31** is used to interface with the device. The display unit **10** also receives power from the device through this interface. The serial port **31** is programmable, which may have a default setting of 9600 BPS. The interface to the display is a serial interface utilizing the industry standard USB cable **26**. About five volts of power may be provided through the USB cable **26**.

The display unit **10** also may include a vacuum fluorescent display **24** having a resolution of 128x64 pixels and an internal speaker **32** which emits a tone to indicate that a key has been pressed. The keypad **34**, speaker **32**, and display **24** may connect to processor **38** via a general purpose input/output interface bus **35** as shown in FIG. 3.

In a diagnostics process, input/output interfaces such as the speaker circuit, display and control keys are tested. In addition, internal and external loop back tests may be performed to determine the integrity of the RS-232 driver chip and all connections on the serial data path and proper operations of serial port communications. In particular, the speaker circuit is tested by turning the speaker from its lowest to highest volume in a fairly rapid succession. The display **24** is tested by illuminating all the pixels on the display **24**. The control keys are tested by displaying the key that was pressed. Diagnostics are preferably initiated by holding down the ENTER key while applying power from the USB cable. The diagnostic title screen and the version of software are displayed when diagnostics are first entered. During the diagnostics, the display unit **10** also provides instructions on how to exit diagnostics.

FIG. 4 is a rear view of the display unit **10** of FIG. 1. As illustrated, the back panel of the display unit **10** includes inner hand grips **44-1**, **44-2** and outer hand grips **42-1**, **42-2**. The hand grips **42** and **44** allow a user to firmly hold the portable display unit **10** with either the left or right hand. Preferably, as illustrated in FIGS. 5A-5C, the user uses both hands to hold the display unit **10**.

The inner and outer hand grips **42**, **44** allow users to firmly hold the display unit so that the user can use one finger to navigate the keys while holding the display in the users' palms. FIG. 5B illustrates the outer hand grips **42-1**, **42-2** providing hand grips to users with small to average hands. FIG. 5C illustrates the inner hand grips **44-1** and **44-2** being used by a user having large hands.

In addition, the inner and outer hand grips **42**, **44** are designed to stabilize the display unit **10** on a horizontal plane. The user can place the display unit on a horizontal plane such as a desk or table and still be able to navigate the keys without the need for holding the display unit down.

FIG. 6 illustrates the rest stand **22** rotated about a horizontal axis perpendicularly extending away from the front side of display unit. The rest stand **22** stabilizes the display unit **10** in an upright position. The rest stand **22** is a constant torque hinged stand to support the display unit **10** in various angular positions. The user can place the display unit **10** on a horizontal surface and use the rest stand to tilt the display unit **10** back to view the display **24** in a preferred angle. As illustrated in FIGS. 5A-5C, the rest stand can be rotated to extend vertically along the side of the display unit **10** so that the user can hold the display unit with his hand.

The display unit **10** can also be mounted on a tripod **72**, as shown in FIG. 7. A screw connector **52** (FIG. 5A) on the bottom of the display unit **10** allows the display unit to securely mount on the tripod **72**. The tripod **72** can be a camera tripod having a rotational mechanism to allow the rotation of the display unit **10**. The tripod provides rotational and elevated views of the display. In addition, the tripod provides more stable placement of the display unit on a horizontal surface. The screw connector **52** also may be used to mount the display unit on a bracket.

Returning to FIG. 1, the display unit **10** is connected to a vacuum network controller **12**. The vacuum network controller **12** includes a display interface library having source codes and files to communicate with the display unit **10**, generate menus specific to the vacuum network controller **12**, and request/receive data from the components and devices of the vacuum network controller **12**. The display interface library is created when the vacuum network controller **12** powers up. In particular, a display driver object is created to interface to the vacuum network controller's dedicated serial drivers. In addition, a display document object is created to interface to data from the vacuum network controller **12**. The display interface also includes a definition of all menus covering programming, controlling and monitoring functions of the vacuum network controller **12**.

A computer-software-based process for interfacing between a device and the display unit **10** is illustrated in the form of a flow chart in FIGS. 8A–8B. In this example, the device is a vacuum network controller **12**. However, as discussed above, the computer-software-based process described below may reside in other system devices to be accessible to the display unit.

When the display unit **10** connects at **802** to the vacuum network controller **12**, the display unit **10** also receives power through the connection **26** (FIG. 2). The display unit initializes at **801**, and at **803**, sends a ready message to the vacuum network controller **12**.

Once the vacuum network controller receives a ready message at **804**, the vacuum network controller **12** initializes at **805**.

If the display unit **10** is disconnected from the vacuum network controller, the vacuum network controller **12** detects that the display unit is no longer connected and resets. For example, the vacuum network controller occasionally sends a test packet to determine whether the display unit is connected. The vacuum network controller **12** monitors the serial port for connection to another display unit.

After initializing the vacuum network controller **12**, an initialization message is sent at **806** to the display unit **10**. If the display unit **10** does not receive the initialization message from the device at **807**, then it sends at **803** another ready message until the initialization message is received. This handshake process indicates that the device and display unit **10** are active and working properly.

After sending the initialization message at **809**, the vacuum network controller **12** may check the revision level of the software embedded in the display unit **10** to determine if the software needs to be updated. If it is determined at **811** that the software needs to be updated, then the vacuum network controller **12** updates at **808** the software of the display unit **10** by downloading at **850**. In addition, special bitmaps that are not stored in the display unit **10** may be downloaded during this time. For example, a welcome logo may be downloaded and displayed.

Referring to FIG. 8B, once initialization process **800** is complete, the vacuum network controller generates at **813** a

menu and sends it at **810** to the display unit **10** (FIG. 1). The display unit **10** receives the menu at **815** and displays it on the display **24** at **817**. The vacuum network controller also sends an acknowledgment message at **818**.

Once the acknowledgment message is received at the display unit at **820**, the display unit **10** receives a key press at **819**. Then, the display unit determines at **823** the key press mode. There are two key press modes, polling key press mode and non-polling key press mode. The display unit **10** and the vacuum network controller **12** are preferably in non-polling key press mode unless the vacuum network controller **12** sends a command to the display unit **10** and puts them in polling mode. In polling key press mode, determined at **814** by a device, the display unit **10** accepts a single key press and stores it in volatile memory at **825** until the vacuum network controller **12** sends a command requesting the key at **830**. Once the display unit **10** receives the request at **832**, the stored key press is sent at **834**. Sometimes, there may be no stored key press.

The polling mode is preferably used for monitor menus because the monitor menus are constantly refreshed and only require a key press to exit the menu. In the polling mode, the vacuum network controller **12** may send new data to the display unit **10** without the chance of collisions with key press packets coming from the display unit **10**. In the non-polling (interrupt) key mode, a key can be pressed at any time and is immediately sent to the vacuum network controller **12** at **827**.

If the menu being displayed is a monitoring menu or, in the polling mode, it is determined at **828** that there is no key press, then, the vacuum network controller **12** refreshes data at **816**, generates a menu with a new set of data at **813**, and sends the menu to the display unit **10**. For example, if the menu is showing the status of compressor **16** including various pressure levels, the vacuum network controller **12** refreshes by requesting for new data and sending the data to the display unit **10**.

Once a key press is sent at **827** from the display unit **10** to the vacuum network controller **12**, the vacuum network controller **12** receives at **812** the key press. The vacuum network controller **12** processes the key press at **822**. For example, if the menu is a monitor menu (FIG. 9B) illustrating data, then typically, the key press is for a new screen. However, if the menu is a set up menu (FIG. 9C), a key press may be requesting a new menu or changing a value. For example, as illustrated in FIG. 9C, the user may be changing the BAUD rate of one of the ports.

The vacuum network controller **12** then determines if the ENTER key was pressed at **824**. If the ENTER key was pressed, then the key press is committed to non-volatile memory at **826**. Otherwise, the key is stored in volatile memory.

After generating a menu at **813**, the vacuum network controller **12** sends or updates the menu to the display unit **10** at **810**. The menu is generated at **813** by changing a value on the menu or providing a new menu. Thus, at **810**, the vacuum network controller **12** sends messages to change a line or a character in the menu. Further, the messages may include a new menu. This loop continues until the display unit **10** is disconnected or screen saver is activated.

The vacuum network controller **12** also supports service session menus. Preferably, these menus are restricted to service personnel. These menus may be restricted by providing access when a password sequence of key entries are made. The service menus provide an interface to the vacuum network controller **12** command parser, so that all commands on the vacuum network controller **12** are directly

accessible via the display unit **10**. It requires familiarity with the interface commands and is a tool in addition to the screens described to allow maximum flexibility. This takes a string provided by the user and sends it to the vacuum network controller **12** as if it were an OR command line interface. The response is sent to the display unit **10** menu as a text string.

As discussed previously, the display unit **10** may be connected to other devices such as cryopump **18** and compressor **16** to support programming, controlling and monitoring all the functions of the device.

Returning to FIGS. 9A–9C, each menu **94** may be split up into multiple horizontal regions. Each region **92** is capable of displaying up to 21 characters of text or more, containing a selector character, title, data and a cursor. There can be multiple regions per line but the total number of characters displayed by any combination of regions on a single line typically do not exceed 21 characters. Different configuration of the menu may be used according to the user's needs.

In general, commands sent from a device require an acknowledgment from the remote display unit **10**. The device can send commands to display text, bitmaps, cursors, check-off boxes, scroll indicators, clear and others. The only commands that the display unit **10** sends are the "ready" command and key press command.

The device includes a definition of all menus specific to the device and the regions within each menu. Each region also may contain a check-off box and an under-bar cursor **96**. The region also defines whether it contains data, the attributes of that data and a pointer to the object that "owns" the region. Menus can have static or dynamic regions. Static regions are created once when the device is initialized and are never deleted, e.g. Main menu. A menu with dynamic regions has regions created each time the menu is accessed, e.g., a list of all pumps on the network.

Each screen may be defined as the view of the display **24** that contains up to (8) lines of text and controlled by making entries at the keypad **34** (FIG. 3). The screens will have common attributes that include identical keypad values (direction, enter, home, etc. keys).

FIGS. 10A–10D are an example tree map of menus for a vacuum network controller **12** connected to a display unit **10**. The tree map and individual menus may be built according to the user's preference and needs. In addition, the tree map and menus may reside in other system devices to be accessible to the display unit **10** and built according to the needs and features of the device.

After the initialization process is completed, a Main menu **100** is displayed from the vacuum network controller **12**. Whenever the HOME button is hit, this screen is displayed. The Vacuum Network Controller **12** Main menu **100** provides options to the following menus: a Monitor menu **104** to monitor various network data and configuration; a Regeneration menu **102** to start regeneration for pumps selected by a user; an Access Device menu **106** to start a session with a pump, or other devices on the network; and a System Setup menu **108** to change and display the configuration of the vacuum network controller **12**.

The Regeneration menu **102** allows the user to start or abort a group regeneration. It also displays the current group regeneration state. This state is simply ON or OFF. An OFF state indicates that a group regeneration has not started or is not in progress. An ON state indicates that a regeneration has started or is in progress. This menu is not a monitor screen, so the menu is preferably refreshed when the screen is entered or navigated. Selecting a "Start" option starts to

regenerate the pumps. Selecting an "Abort" option stops a group regeneration that is already in progress.

Once the "Start" option is selected, the user enters a Choose Regen Pumps menu **110** showing a list of all pumps currently on the vacuum network. The user is allowed to select pumps to regenerate. If the BACK or HOME key is hit before the "ENTER" option is hit, the display returns to the Main menu and changes made at this screen is discarded.

A List to Regen menu **112** displays all pumps that were selected in the Choose Regen Pumps menu **110** to be regenerated. If the user is satisfied with the list and would like to proceed, the user selects either "start fast regen" or "start full Regen" option and hits the ENTER key. If the ENTER key is pressed, the vacuum network controller **12** starts a group regeneration. If the user is not satisfied and wishes to edit the list, the user may return to the previous menu by pressing the BACK key.

A REGEN Verification menu **114** prompts the user to confirm starting a regeneration. It provides a simple choice to start a Regen or not. If the user decides not to start a Regen, then the user is returned to the previous menu screen and no Regen is started. Otherwise, a FAST REGEN STARTED menu **116** is displayed or a Regen Response menu **118** displays the results and includes an error message if the command fails.

A Regeneration Abort menu **142** provides the user a chance to verify that they want to abort regeneration.

The Monitor Network menu **104** provides access to other menus which display readable data. The data may include both configuration and runtime pump data. This family of menus may be expanded to include other menus according to the user's needs. The data displayed in this branch of menus is refreshed by the vacuum network controller **12** at regular time intervals. In addition, since these menus are monitor menus, they are in poll-key press mode.

A Network Devices menu **124** of FIG. 10D displays a list of the type and quantity of devices that are on the network. The user can scroll to the type of device they wish to view and hit the ENTER key to proceed to the next menu which identifies each of these devices. For example, a Network Pumps menu **126** identifies every pump on the network and a Network Compressors menu **128** identifies every compressor on the network.

A Regeneration menu **132** allows the user to peruse the roughing maps and other regeneration configuration data. To view the roughing maps, the user hits enter and is taken to a screen that shows a Rough Map **1** menu **134**. The user can navigate through all maps from that screen.

A Network Status menu **130** provides options to monitor device parameters across the network. The options may include a Pump Temperatures menu **136** which provides T1 (first stage) and T2 (second stage) temperatures for all pumps on the network. For example, pump **1** has T1 and T2 temperatures of 35 K and 12 K respectively. The Network Status menu **130** may also include other device parameters for each pump. A Compressor Pressures menu **140** displays the Supply and Delta pressure for all compressors on the network.

A Network Status menu **138** indicates the status of the network. The vacuum network controller **12** scans the network and return a list of all devices on the network. Any problems that are discovered are flagged, otherwise the user receives an indication that the network is operating correctly. Preferably, the Network Status menu **138** does the following: scan the network for all devices; verify every device on the network is also on a helium map; indicate all devices on the network and in the helium map with the Serial Number

11

and Software Revision; devices that are on the network but are not in a helium map are flagged; and devices that are not on the network but are in a helium map are also flagged.

A Helium Management menu **142** provides a Show Helium Maps menu option for a Show Helium Maps menu **144** that allows the user to view each Helium Map.

The Access Network Device Screen **106** of FIG. **10B** allows the user to access an individual pump or other network devices such as a cryopump. The user initially selects the type of devices to access. The quantity of each type of device currently on the network are displayed. An option to switch a device “on” and “off” may also be included. The user may scroll to the device and access it by hitting the ENTER key. An Access Network Pumps **146** menu allows the user to select a pump number from a list of pumps on the network and open a session with the selected devices. The display unit **10** then accesses the pumps directly, and the vacuum network controller **12** transfers data between the two. Thus, the menu maintenance stays within the device that provides the menus.

The user sees a list of pumps on the network and selects one with the cursor. After the enter button is hit, the Pump session is launched. If the pump is directly connected to another display unit, then the pump locks the local display unit. The lock on the local display unit is released when the session is terminated. The pump’s local remote display (RD) displays the Pump Main menu. The pump session on the vacuum network controller **12** appears as if the display unit **10** were directly plugged into the pump. The vacuum network controller **12** is able to detect if the pump is no longer able to communicate with the vacuum network controller **12** (from a network error or the pump being taken offline) during a session and terminates the session. An intermediary screen may be provided to choose the type of device.

The Access Pump menu **147** is a monitor-like screen that contains Temperature **1**, Temperature **2**, Cryo TC (Vacuum) and current Regen Status. The Access Pump menu **147** may also include other pump data.

Access Network Compressor menu **148** is similar to the Access Network Pump menu **146** and provides similar data of compressors on the network.

A Compressor Data menu **149** is provided until compressor sessions are supported.

The System Setup menu **108** includes menus that are configured and generally not accessed by the user. The Password Setup menu **156** sets up a user password to enter all menus except the monitor menu. The Regen Config menu **150** includes all regeneration related configurations. The Data Communication menu **162** sets data communication parameters and provides a hidden entry into virtual command interface sessions.

The Regeneration Setup menu **150** provides the configuration of regeneration parameters. To configure a rough map, the user scrolls to that region, hits ENTER, and scrolls the map ID’s until getting to the one desired. The user then hits ENTER again to go to the configuration screen. Full coordination and Power Failure Coordination are also set on/off by scrolling on this screen.

A Rough Map menu **152** allows the user to configure the map by selecting or deselecting the pumps to be members of the map and hitting ENTER to create the map. All pumps on the system are displayed. The pumps already in the map may be removed from the list or left on it.

After selecting the pumps for the map, the user scrolls down to “ENTER” and hits enter to create the rough map.

12

Before entering the change, the user may hit the BACK key or HOME key to cancel the change. The configuration is not changed until the “COMMIT CHANGE” option is chosen on the next screen and the ENTER key is hit. If an error prevents the rough map from being configured, a menu informs the user and returns to the last screen to reconfigure the map.

A Password Setup menu **156** of FIG. **10C** allows the user to select password protection by selecting “Change Password” option to set a password and turning “Protection” on. When the user turns Protection on, the user is prompted to set the password. The Enter Password menu **158** allows a user to enter a password. The Confirm Password menu **160** confirms the password. To enter any branch off the main screen except the “Monitor” menu, the password is required. When Protection is turned off, no password is required.

A Secret Password Reset feature, as shown in FIG. **10B**, may be provided to reset the password to a default value. The user may reset the password in case the password is forgotten, without requiring field support. The password reset function is implemented from the main screen by pressing a combination of keys. When a correct combination of keys are pressed, e.g. a “hidden command,” a Warning menu asks the user if he wants to reset the password. By pressing the Enter key, password reset is completed and Caution menu **122** is displayed.

At the Confirm Password menu **160**, as shown in FIG. **10C**, the user may hit the Back key before committing the data if he decides not to change or set a password. If confirmation fails, then an error message may result. If confirmation is successful, then a message indicating success may be displayed. There may be pop-up screens to guide the user if the entered password is not within the required range.

A Data Communication menu **162** provides access to the communication parameters. The vacuum network controller determines which ports are available. The user may change a value by scrolling to the parameter and setting a new value.

There may be several hidden screens that can be accessed from the COMMUNICATION screen by hitting a combination of keys or keys in sequence. The hidden screens allow service personnel to access data that the user either does not need to access, because it is easily misinterpreted and may not be significant to their operation, or should not access, because unintended misuse could have a negative impact on their system.

The Hidden screens may be entered via the Service Info menu **164** which include options to view Map data or enter a Virtual command interface session.

A Hidden Virtual Command Session menu **166** is a yes/no verification menu to verify whether the user wishes to enter a session.

A Virtual Command Session menu **168** may include two boxes. The first one may be to enter commands to the vacuum network controller **12** and the second one may be to see the vacuum network controller’s response to the command.

A Hidden Helium Map menu **170** of FIG. **10C** displays data that the user does not need to access. A Helium Setup menu **172** allows the user to select which Helium Map they want to configure by entering the number. Numbers are scrolled like other screens with the UP/DOWN arrow keys and committed by pressing the ENTER key. A Choose Helium Map Pumps menu **174** is similar to the Rough Map menu **152** and allows the user to select pumps. A Choose Helium Map Compressors menu **176** is similar to the Rough Map menu **152** and Choose Helium Map Pumps menu **174**

13

and allows a user to select compressors. A Verify Helium Map Setup menu **178** displays the Helium Map and allows the user to accept (COMMIT) or reject it. The Verify Helium Map Setup menu **178** is similar to the Verify Rough Map Menu **154**.

FIG. **11A** is an example tree map of menus for a cryopump **18** connected to a display unit **10-5**.

A Pump Main menu **200** displays the name of the device, and provides the user with options to enter the following menus: a Monitor menu **202** which monitors temperature and pressure values, temperature control parameters, and regeneration status; a Regeneration menu **204** for starting, stopping, or aborting a full or fast regeneration; a System Setup menu **206** which allows configuration of Regeneration setup, Security, Communication, Station ID, Power Fail Recovery parameters, and Relays; a Control menu **208** which allows manual control of various parts of the Cryopump; a Pump Info menu **210** which displays information about Software revisions, serial number, part number, address and operating time.

FIG. **11B** illustrates an example Cryopump Monitor menu tree map. The Monitor menu **202** allows access to children menus to view information on Pump State **212**, Regeneration Information **214**, Valve Status **216** and Temperature control **218**.

FIG. **11C** illustrates an example Cryopump Regeneration menu tree map. The map includes the Regeneration start menu **204** to confirm starting regeneration, a Regen Verification menu **220**, a Regeneration status menu **222**, a Abort Regeneration menu **224** for aborting regeneration in progress, and Regeneration Response menu **226**.

FIG. **11D** is an example tree map of Cryopump System Setup menus. The System Setup Main menu **206** provides a Regeneration Setup menu **230** providing a selection of regeneration setup categories, including regeneration purge setup, regeneration roughing setup and regeneration delay setup. The System Setup menu **206** also provides an option to a Security Setup menu **232**, a Station ID menu **236** to identify the station, a Power Fail Setup menu **238** to configure Power Failure parameters, a Communication Setup menu **234** and a Relay Setup menu **240** to select a relay to configure.

The Control menu **208** (FIG. **11A**) allows the user to control various parts of the cryopump including motor, rough value, purge value, vent valve and relays. The Pump Info menu **210** allows the user to view pump serial number, part number, network address, operating time and software revision.

The user may also access a Service menu by pressing a combination of keys or keys in a sequence. The menu includes information about Management parameters, Temperature Control Parameters, and Software versions for the individual modules in the pump. In addition, the menu may provide access to hidden menus for entering a virtual command session.

Referring back to FIG. **1**, the menus for the cryopump **18** also may be accessed and displayed on the remote display unit **10-1** that is connected to the vacuum network controller **12** through a remote session. Similarly, the remote session may be made with other devices to provide access and display menus of the selected device on the remote display unit **10-1**. For example, the user may create a remote session from the vacuum network controller **12** by navigating to a menu which allows the user to choose a device such as a cryopump **18**, waterpump **10**, turbopump **15**, gauges **17**, compressor **16** or roughing pump **14** on the network, and start a remote session.

14

The devices and vacuum network controller **12** communicate with each other over the network using the bitbus master/slave protocol. When the vacuum network controller **12** is designated as the master, the devices respond to requests from the vacuum network controller **12**. Thus, in a remote session, the vacuum network controller **12** is used to drive the session. The vacuum network controller **12** may perform this in a loop:

Send request (bitbus) to the device for a command;  
If got command, send it to the remote display unit (serial) and get response (serial);  
Send the remote display unit's response to the device (bitbus);  
Start over.

When a device receives the vacuum network controller's open session request but already has a display unit **10-5** directly plugged into it, the device locks out the display unit **10-5** and displays a message to the user that there is a remote session running. If, at the time of open session request, there is no local display unit directly connected to the device, but a display unit is connected after a remote session has started, then the local display unit directly connected to the device is locked out and the remote session message is displayed.

Since the device can send commands to the vacuum network controller **12** at vacuum network controller's request, the vacuum network controller **12** sends a command to the device over bitbus asking the device if it has any commands for the remote display unit **10-1**. The vacuum network controller **12** also sends different commands to return responses from the remote display unit **10-1** to the device.

A display unit **10** communicates using packets that can vary in length. Packets having 4 to 25 bytes are used, but packets of other sizes may also be used. The bitbus protocol used in the network may be set up to send 13 byte packets. However, the bitbus protocol can also be configured for different packet lengths.

To get around this restriction on the payload length of the bitbus packets, serial packets from the display unit **10** are fragmented and reassembled after sending them over the bitbus network. For example, in a remote session with the cryopump **18**, the cryopump **18** breaks a serial packet, which is meant for a local display unit **10-5**, up into fragments if it is greater than 13 bytes and sends it to the vacuum network controller **12**. In particular, each serial packet, or fragment of a packet has length added to it at the beginning of the packet. The serial packet is then embedded into a bitbus packet, and sent over the bitbus network to the vacuum network controller **12**. The vacuum network controller **12** gets the packet and reconstructs the fragments into a single serial packet. The vacuum network controller **12** then sends the serial packet to the remote display unit **10-1**.

Similarly, when the vacuum network controller **12** receives a response from the remote display unit **10-1**, the vacuum network controller **12** embeds the response into a bitbus packet and sends it to the cryopump **18** appended onto a command string which indicates that this is a response from the remote display unit **10-1**. Thus, the remote display unit **10-1** attached to the vacuum network controller **12** receives serial commands and sends responses without knowing that the origin is a device somewhere else on the network. In addition, the packets and responses may be stored in buffers on the device.

To close a remote session, the user may hit a BACK key from the device's main menu. The device then sets a command to close the session and sends the command to the vacuum network controller **12** at the next vacuum network

## 15

controller's request. The vacuum network controller **12** then gets the close command and sends the close session command to the device so the remote session is closed.

As stated above, a remote session may be established between the remote display unit **10-1** connected to the vacuum network controller **12** and any device such as a waterpump **19**, cryopump **18**, turbopump **15**, gauges **17**, compressor **16**, or roughing pump **14**.

While this invention has been particularly shown and described with references to preferred embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims.

What is claimed is:

**1.** A method of communicating with plural devices comprising:

storing a display controller in each of plural devices of different types, each display controller generating display menus specific to the type of device;

providing a portable display unit having a display and control keys;

connecting the portable display unit to a first device of a first type, selected from the group consisting of a vacuum network controller, a cryopump, a roughing pump, a compressor, a water pump, a gauge and a turbopump, receiving menus from the first device specific to its type, displaying the menus on the portable display unit, and forwarding messages to the first device from the portable display unit to indicate activation of control keys; and

connecting the portable display unit to a second device of a second type, receiving menus from the second device specific to its type, displaying the menus on the portable display unit, and forwarding messages to the second device from the portable display unit to indicate activation of control keys.

**2.** The method of claim **1** wherein the second device is selected from the group consisting of a vacuum network controller, a cryopump, a roughing pump, a compressor, a water pump, a gauge and a turbopump.

**3.** A method according to claim **1**, further comprising: establishing a remote session between the portable display unit and the first device.

**4.** The method of claim **3** wherein the plural devices are used in a fabrication plant.

**5.** A method according to claim **1**, further comprising: receiving menus from the first device specific to its type, displaying the menus on the portable display unit, and forwarding messages to the first device from the portable display unit which is connected to the second device to indicate activation of control keys.

**6.** A method according to claim **1**, wherein the display menus include hidden menus specific to the first device.

**7.** The method of claim **6** wherein the display menus include menus to monitor the first device.

**8.** The method of claim **6** wherein the hidden menus provide a command interface.

**9.** A method of communicating with plural devices comprising:

storing a display controller in each of plural devices of different types, each display controller generating display menus specific to the type of device;

providing a portable display unit having a display and control keys;

connecting the portable display unit to a first device of a first type, receiving menus from the first device specific

## 16

to its type, displaying the menus on the portable display unit, and forwarding messages to the first device from the portable display unit to indicate activation of control keys;

connecting the portable display unit to a second device of a second type, receiving menus from the second device specific to its type, displaying the menus on the portable display unit, and forwarding messages to the second device from the portable display unit to indicate activation of control keys;

initializing the portable display unit and the first device subsequent to connecting the portable display unit to the first device to assure proper connection between the portable display unit and the first device; and

checking software on the display unit to determine whether the software version is compatible with the one on the first device.

**10.** The method of claim **9** further comprising the step of forwarding bitmaps specific to the first device.

**11.** A device comprising:

a processor;

a display interface in communication with the processor, the display interface providing a connection to a display unit;

a computer-readable medium in communication with the processor, the computer-readable medium storing computer-executable software code for:

providing a display driver for communication with the display unit;

generating a first menu specific to the device;

communicating the first menu to the display unit for display;

receiving a key entry from the display unit;

processing the key entry;

generating a second menu in response to the key entry; and

communicating the second menu to the display unit for display.

**12.** The device of claim **11** further comprising software code for committing the key entry upon activation of the enter key.

**13.** The device of claim **11** wherein the device is selected from the group consisting of a vacuum network controller, a cryopump, a roughing pump, a compressor, a waterpump, a gauge and a turbopump.

**14.** The device of claim **11** wherein the display interface is a serial port.

**15.** The device of claim **11** further comprising software code for retrieving monitor data from device components.

**16.** The device of claim **15** wherein the software code generates the second menu by refreshing monitor data in the first menu.

**17.** The device of claim **11** wherein the software code generates the second menu by changing set data in the first menu.

**18.** A method for displaying a menu on a portable display unit comprising:

connecting the portable display unit to a device;

initiating the display unit and the device to assure a proper connection between the display unit and the device; at the device, generating a first menu and communicating the first menu to the display unit;

from the display unit, forwarding a key entry; and

at the device, processing the key entry, generating a second menu in response to the key entry, and communicating the second menu to the display unit.

**17**

**19.** The method of claim **18** further comprising resetting the device when the portable display unit is disconnected from the menu.

**20.** The method of claim **18** further comprising periodically forwarding initialization messages from the device to the display unit to assure a proper connection between the display unit and the device.

**21.** The method of claim **18** further comprising at the display unit, receiving the first menu from the device and displaying the menu.

**18**

**22.** The method of claim **18** wherein second menu is the menu having refreshed data.

**23.** The method of claim **18** further comprising at the display unit, the step of receiving a key request from the device.

**24.** The method of claim **18** wherein the second menu is a new menu with different regions and data.

\* \* \* \* \*